



921459.003

Serie: Industrial Hall Highbay luminaires

Type of Installation: Suspension cable/chain
Type of Protection: **IP 65**
Protection Class: I
Lamp/Wattage: 1 x LED 124,8 4000 K / 14750 lm
Dimensions: D 570, H 533
Colour: black

Housing: die cast aluminium, black powder coated, with eye ring.
Passive cooling. Cover: transparent single pane safety glass (toughened glass). Primary light control with high performance wide area LEDs in light colour 840. Refractor: transparent plastic, prismatic on the outside. Suited for chain or steel cable suspension (provided by the client).

Electrotecnia:

Electric Gear Converter
Voltage 230 / 50 Hz
System Power 133 W

Autorizaciones:

Type of Protection **IP 65**
Protection Class I
Glow Wire Test 960°C - 30 seconds
Impact Protection (IK-Value) IK07 (2 Joule)
Safety Marks F-mark, D-mark
Other Marks WEEE mark
Country Code CE
Energy Efficiency Class LED A++
Energy Efficiency Class of included lamp A++

Lámpara 1:

Lamp LED
Socket
Colour Temperature 4000K
Light colour 840
Number of Lamps 1
Lifespan 50000 h (L70/B10)

Lámpara 2:

Lifespan lamp

Medidas y pesos:

Diameter D 570 mm
Height H 533 mm
Suspension Length
Ceiling Thickness
Weight 9,72 kg

Técnica de iluminación:

Luminaire Beam Angle 70°
Luminaire flux 14.800 lm
Colour Rendering Index (CRI) 80

Accesorios

Ceiling and wall mounting bracket

982112.003 black

Piezas de recambio

Refractor: plastic

982115.000 D 570, H 343 transparent